Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Liquid Elements Shieldwax Hybrid Wax
- · UFI: CR10-90KD-E000-24MP
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Car polish

Maintenance product

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

AREA 52 GmbH Thüngenfeld 4 D-58256 Ennepetal

Germany

tel. +49-(0)2333-3068945

e-mail: info@liquidelements.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: tel.: +49 (0)2333-3068945 (Monday to friday: 8:00 17:00)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

2-methyl-2H-isothiazol-3-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container to an authorised waste disposal contractor or licensed local authority disposal / landfill site.

(Contd. on page 2)

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PRT:

The product does not contain any PBT (PBT: persistent, bioaccumulative, toxic) substance or does not fulfil criteria for PBT according to annex XIII of regulation (EC) 1907/2006 (< 0,1%).

· vPvB:

The product does not contain any vPvB (vPvB: very persistent, very bioaccumulative) substance or does not fulfil criteria for vPvB according to annex XIII of regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 57-55-6 EINECS: 200-338-0 Reg.nr.: 01-2119456809-23	Propylene glycol substance with a Community workplace exposure limit	10-<20%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C≥50 %	1-<2%
CAS: 75718-16-0 EC number: 616-256-7	Aminomodified Polydimethylsiloxane Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<2%
CAS: 68920-66-1 Polymer	Alcohols, C16-18 and C18-unsaturated, ethoxylated Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315	0.1-<1%
CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 2, H330 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411 Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	0.0015-<0.01%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: If symptoms persist consult doctor.
- · After inhalation: Fresh air. If pain persists, get medical attention.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Immediately flush eyes with plenty of water with lids lifted. If symptons persist, seek medical advice.

· After swallowing:

Rinse out mouth with water.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

- G

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Full water jet
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Silicium dioxide

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

· 6.2 Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Observe the usual precautionary measures for handling chemicals.

Avoid contact with eyes.

Avoid close or long term contact with the skin.

Observe use instructions.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in dry conditions at 10 - 25 °C.

Protect from frost.

- · Storage class: 10 13 (Germany)
- · 7.3 Specific end use(s) No further relevant information available.

GB

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

57-55-6 Propylene glycol

WEL Long-term value: 474* 10** mg/m³, 150* ppm *total vapour and particulates **particulates

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Observe the usual precautionary measures for handling chemicals.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves according EN 374.

Check the permeability prior to each anewed use of the glove.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time: ≥ 480 minutes (Permeation according to EN 374 Part 3: Level 6)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

- · Eye protection: Goggles recommended during refilling
- · Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
 Colour: Yellowish
 Odour: Mild

(Contd. on page 5)

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

	(Co	ontd. of pag
Odour threshold:	Not determined.	
pH-value at 20 °C:	~ 6	
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Not determined. 100°C	
Flash point:	> 60 °C (Analogieschluss)	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits: Lower: Upper: Oxidising properties	Not determined. Not applicable.	
Vapour pressure:	Not determined.	
Density at 20 °C: Relative density Vapour density Evaporation rate	~ 1.01 g/cm³ Not determined. Not determined. Not determined.	
Solubility in / Miscibility with water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
Solvent content:		
Solids content: 9.2 Other information	Not determined. No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Protect from frost.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	0 values rei	levant for classification:
57-55-6	Propylene g	glycol
Oral	LD50	2,000 mg/kg (rat)

(Contd. on page 6)

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

		(Contd. of page 5)
Dermal	LD50	20,800 mg/kg (rabbit)
64-17-5 eti	hanol	
Oral	LD50	10,470 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	117-125 mg/l (rat) (OECD 403)
75718-16-	0 Aminom	odified Polydimethylsiloxane
Oral	LD50	>2,000 mg/kg (rat)
		>2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Repeated dose toxicity

64-17-5 ethanol

Oral 90-day feeding study 1,730 mg/kg bw/day (rat) (OECD 408)

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

64-17-5 ethanol

Ames test negative (bacterial reverse mutation assay)

- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity: 64-17-5 ethanol EC50 9,000 mg/l (algae) (Chlorella pyrenoidosa (10 d)) LC50 12,340 mg/l (daphnia magna) (48 h) 4,600 mg/l (fish) (96 h, Leuciscus idus melanotus)

12.2 Persistence and degradability

The solvent is biodegradable

The contained surfactants are easily biodegradable

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

GF

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Smaller quantities can be disposed of with household waste.

Dispose of in accordance with all applicable local and national regulations.

· Europear	n waste catalogue
07 02 17	waste containing silicones other than those mentioned in 07 02 16
15 01 02	plastic packaging

- · Uncleaned packaging:
- · Recommendation:

Dispose of in accordance with all applicable local and national regulations.

Non contaminated packagings may be recycled.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport informa	tion	
14.1 UN-Number ADR, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann Marpol and the IBC Code	n ex II of Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed, if applicable.

(Contd. on page 8)

Printing date 09.12.2020 Version number 3 Revision: 09.12.2020

Trade name: Liquid Elements Shieldwax Hybrid Wax

(Contd. of page 7)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out, because it is not necessary for mixtures.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Liability excluded.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

CLC GmbH

Simonshöfchen 55

D-42327 Wuppertal

Tel.: +49-(0)202 - 87018691

· Contact: Mr. Sven Rosendahl · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

CLP: Classification, Labelling and Packaging (Regulation (EC) No. 1272/2008

REACH: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.

EC50: effective concentration, 50 percent

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

VCI: Verband der chemischen Industrie, Deutschland (German chemical industry association)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity - oral – Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 2: Acute toxicity - inhalation - Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

· * Data compared to the previous version altered.